



IP + IK Storm LED IP66 Wide 145



- The Storm LED IP66 Wide145 can be Surface Mounted on the wall and/or Suspended from the ceiling
- Choose the wide body to retain uniformity where required
- Wire Suspension available
- Storm is suitable for Carparks, Cool Rooms and any place that a weatherproof luminaire is required
- LED Outputs and LED Lamp Colour options available
- IP66
- IK08
- Not recommended for open rooftops
- Luminaire lifetime L80/B10 >60,000hours
- MacAdams 3 SDCM
- Ta: - 5°C to 35°C

Options

- Ultra Dim (Extra Low Dimming to 0.1%)
- Dim (Dali Dimming to 1%)
- WS (3m Wire Suspension Kit)
- LSL-R (LSL 10a Relay) For internal use only
- LSL-SS (LSL with Switch Dim) For internal use only
- LSL-SS30 (LSL with Switch Dim and 30 Minute Turn Off) For internal use only
- 90+CRI




Eg Code STM-SM-1200-36w-3K-W145



Code	Absolute Lumens	Dimensions	
	4K	A	B
STM - SM - 600 - 13w - (2.7 or 3 or 4K) - W145	1425Lm	580	390
STM - SM - 600 - 19w - (2.7 or 3 or 4K) - W145	2162Lm	580	390
STM - SM - 1200 - 23w - (2.7 or 3 or 4K) - W145	2850Lm	1180	800
STM - SM - 1200 - 36w - (2.7 or 3 or 4K) - W145	4359Lm	1180	800

LED PRODUCT LEGEND

STM - SM - 1200 - 36W - 3K - W145					
RANGE	MOUNTING	LENGTH	SYSTEM WATTS	LED COLOUR	Extension



Standard Version

