





# Linear 100 Surface Mount

- Linear 100 Surface Mount is a ceiling mounted luminaire
- Can be wire suspended to give a notable presence
- Easily clipped onto UniStrut extrusion prewired power-in/power-out. With Sensors and Emergencies wired in if required
- Selection of optics throughout the range
- LED Outputs and LED Lamp Colour options available
- Wedge diffuser available
- Wall Wash version available
- Easily off set for corridor lighting
- Cost effective compared to the 300 wide fittings (smaller footprint)
- Luminaire lifetime L80/B10 >60,000hours
- MacAdams 3 SDCM

### Options

- Ultra Dim (Extra Low Dimming to 0.1%)
- Dim (Dali Dimming to 1%)
- EM-LED (LED Emergency) c0 D20 / c90 D20
- EM-LED-EDALI (Monitored option) c90 D20
- LSL (LimeLite Sensor Light)
- WS (3m Wire Suspension Kit)
- USC (UniStrut Clips)
- ER (Earthquake Resistant)
- 90+CRI

Eg Code LIN-SM-LO-1200-23w-3K



Code	Absolute Lumens		Dimensions	Extra Length
	LO	XLG	A	Sensor or EM
LIN - SM - (LO OR XLG OR FL) - 600 - 13w - (2.7 or 3 or 4K)	1280Lm	1125Lm	590	610
LIN - SM - (LO OR XLG OR FL) - 600 - 19w - (2.7 or 3 or 4K)	1882Lm	1656Lm	590	610
LIN - SM - (LO OR XLG OR FL) - 600 - HO - (2.7 or 3 or 4K) HO	2130Lm	1891Lm	590	610
LIN - SM - (LO OR XLG OR FL) - 900 - 17w - (2.7 or 3 or 4K)	1870Lm	1645Lm	890	910
LIN - SM - (LO OR XLG OR FL) - 900 - 26w - (2.7 or 3 or 4K)	2700Lm	2376Lm	890	910
LIN - SM - (LO OR XLG OR FL) - 1200 - 23w - (2.7 or 3 or 4K)	2537Lm	2232Lm	1190	1210
LIN - SM - (LO OR XLG OR FL) - 1200 - 36w - (2.7 or 3 or 4K)	3716Lm	3270Lm	1190	1210
LIN - SM - (LO OR XLG OR FL) - 1200 - HO - (2.7 or 3 or 4K) HO	4260Lm	3782Lm	1190	1210

### LED PRODUCT LEGEND

LIN	-	SM	-	LO	-	1200	-	23W	-	3K
RANGE		MOUNTING		DIFFUSER		LENGTH		SYSTEM WATTS		LED COLOUR



3m adjustable wire (WS option)

