


Linear 100 **Klean 44** Sealed IP44 Unit

- IP44 Plaster Recess sealed luminaire for areas such as Kitchens, Laboratories and anywhere you require a sealed unit.
- Linear 100 has the ability to be moved small increments to miss objects in the ceiling.
- Selection of optics throughout the range.
- LED Outputs and LED Lamp Colour options available
- Luminaire lifetime L80/B10 >60,000hours
- MacAdams 3 SDCM

Options

- Ultra Dim (Extra Low Dimming to 0.1%)
- Dim (Dali Dimming to 1%)
- SR (Seismic Restraints)
- 90+CRI

Eg Code LIN-PKL-LO-1200-23W-3K



Code	Absolute Lumens		Dimensions	Plaster Cut Out
	LO	XLG	A	L x W
LIN - PKL - (LO OR XLG) - 600 - 13W - (2.7 or 3 or 4K)	1612Lm	1404Lm	630	600 x 115
LIN - PKL - (LO OR XLG) - 600 - 19W - (2.7 or 3 or 4K)	2356Lm	2052Lm	630	600 x 115
LIN - PKL - (LO OR XLG) - 1200 - 23W - (2.7 or 3 or 4K)	2750Lm	2395Lm	1230	1200 x 115
LIN - PKL - (LO OR XLG) - 1200 - 36W - (2.7 or 3 or 4K)	4464Lm	3888Lm	1230	1200 x 115

LED PRODUCT LEGEND

LIN	-	PKL	-	LO	-	1200	-	23W	-	3K
RANGE		MOUNTING		DIFFUSER		LENGTH		SYSTEM WATTS		LED COLOUR



Torsion Spring / Detail



Mounting Screw / Detail