



Description

Linear 100 Plaster Recess is a recessed Luminaire, suitable for a plaster ceiling with a textured white frame. Also fits different thickness of ceiling (timber panels etc). Selection of optics throughout the range. Optional extras – Clutter free the ceiling. Add Emergency + sensor, the encapsulated devices designed to blend in with our luminaires. One point of contact and no switch required for the wall.

Features

- Linear 100 Plaster is a recessed Luminaire, suitable for a plaster ceiling with a textured white frame.
- Suits 10mm-13mm ceiling thickness
- Selection of optics throughout the range
- LED Outputs and LED Lamp Colour options available
- Wedge diffuser available
- Wall Wash version available
- Trim colours available (powder coated) Dulux Mannex White (standard)
- LED CRI >80 as standard
- LED 90+ CRI available on request
- Seismic Restraints available on request
- Cost effective compared to the 300 wide fittings (smaller footprint)
- Luminaire lifetime L80/B10 >72,000hours
- MacAdams 3 SDCM
- XLG Diffuser UGRmax: UGR<19

Photometrics



Options

- Ultra Dim (Extra Low Dimming to 0.1%)
- Dim (Dali Dimming to 1%)
- EM-LED (LED Emergency) CO-D20 (0.2 LUX)/C90-E50 (0.2 LUX)/ CO/C90-E50 (1 LUX)
- EM-LED-DALI (Monitored option) CO-D20 (0.2 LUX)/C90-E50 (0.2 LUX)/ CO/90-E50 (1 LUX)
- LSL (LimeLite Sensor Light)
- SR (Seismic Restraints)
- 90+CRI

Code	Absolute Lumens		Dimensions		Plaster Cut Out
	LO	XLG	A	B	L x W
LIN - P - (LO or XLG) - 600 - 13w - (2.7 or 3 or 4K)	1612Lm	1404Lm	615	584	605 x 105
LIN - P - (LO or XLG) - 600 - 19w - (2.7 or 3 or 4K)	2356Lm	2052Lm	615	584	605 x 105
LIN - P - (LO or XLG) - 900 - 17w - (2.7 or 3 or 4K)	2108Lm	1836Lm	915	884	905 x 105
LIN - P - (LO or XLG) - 900 - 26w - (2.7 or 3 or 4K)	3224Lm	2808Lm	915	884	905 x 105
LIN - P - (LO or XLG) - 1200 - 23w - (2.7 or 3 or 4K)	2750Lm	2395Lm	1215	1184	1205 x 105
LIN - P - (LO or XLG) - 1200 - 36w - (2.7 or 3 or 4K)	4464Lm	3888Lm	1215	1184	1205 x 105