


Standard Frame with
Emergency or Sensor Option Dimensions



Plaster Cut out Dimensions



Description

Square 600 Plaster is a recessed Luminaire, suitable for a plaster ceiling with a textured white frame. Air Handling available on two or four sides. Delivering high quality illumination with great uniformity. Optional extras – Clutter free the ceiling. Add Emergency + sensor, the encapsulated devices designed to blend in with our luminaires. One point of contact and no switch required for the wall.



Features

- Square 600 Plaster is a recessed Luminaire, suitable for a plaster ceiling with a textured white frame
- Supplied with a 2m flex and plug for quick and easy installation
- Air Handling available on two or four sides enables Sensors or Emergency or both in the design
- Selection of optics throughout the range
- LED Outputs and LED Lamp Colour options available
- XLG Diffuser UGRmax: 16
- LO Diffuser URGmax: 22
- Luminaire lifetime L80/B10 >60,000hours
- MacAdams 3 SDCM
- IP rating IP20

Options

- Ultra Dim (Extra Low Dimming to 0.1%)
- Dim (Dali Dimming to 1%)
- EM-LED (LED Emergency) CO-D20 (0.2 LUX)/C90-E50 (0.2 LUX)/ CO/C90-E50(1 LUX)
- EM-LED-EDALI (Monitored option) CO-D20 (0.2 LUX)/C90-E50 (0.2 LUX)/ CO/C90-E50(1 LUX)
- LSL (LimeLite Sensor Light)
- AH (Air Handling)
- 90+CRI (COI Compliant)
- PKL (IP44 Clean Room)

Photometrics



CODE	ABSOLUTE LUMENS	DEPTH (A)	PLASTER CUT OUT (L X W)
SQ - P - LO - 600 - 21W - (3K or 4K)	2613 lm	80mm	530 x 530 mm
SQ - P - XLG - 600 - 21W - (3K or 4K)	2211 lm	80mm	530 x 530 mm
SQ - P - LO - 600 - 26W - (3K or 4K)	3140 lm	80mm	530 x 530 mm
SQ - P - XLG - 600 - 26W - (3K or 4K)	2754 lm	80mm	530 x 530 mm
SQ - P - LO - 600 - 29W - (3K or 4K)	3645 lm	80mm	530 x 530 mm
SQ - P - XLG - 600 - 29W - (3K or 4K)	3086 lm	80mm	530 x 530 mm